

# Declaration of Performance

EC Construction Products Regulation  
EN 12326 Roofing & Cladding Slate



**PRIMERA**  
FINEST NATURAL SLATE

86 Ramsey Road  
Warboys  
Huntingdon  
Cambridgeshire  
PE28 2RW  
Tel: +44 (0)1487 825 222  
Fax: +44 (0)1487 825 240  
info@primeraslate.co.uk  
[www.primeraslate.co.uk](http://www.primeraslate.co.uk)

DOP Number:		DOP 20/003		
1. Unique identification code of the product-type:		Abejeda Zamora (Estella)		
2. Type, batch or serial number or any other element allowing identification of the construction product:		30X20 35x20 40x20 40x25 50x25 50X30 60X30		
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:		Slate for discontinuous roofing and cladding		
4. Name, registered trade name or registered trade mark and contact address of the manufacturer:		Pizarras La Luz S.L. La Ermita 1 Riofrio de Aliste Spain		
5. Where applicable, name and contact address of the authorised representative:		N/A		
6. System or systems of assessment and verification of consistency of performance of the construction product:		System 4		
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:		The manufacturer has carried out factory production control and determination of product type based upon System 4 within the Assessment of Conformity Tasks.		
8. In case of the declaration of performance concerning a construction product covered by a European Technical Assessment:		N/A		
9. Declared Performance:				
Essential Characteristic for Pitched Roof Coverings:	Performance:	Harmonized Technical Specification:		
Mechanical Resistance:	Mean Failure Load:	EN12326-2:2011		
	Transverse: 857.6 N			Longitudinal: 1127.6 N
	Characteristic MOR:			
	Transverse: 62.4 Mpa			Longitudinal: 75.6 Mpa
External Fire Performance:	Deemed to satisfy	EC Decision 2000/553/EC		
Reaction to Fire:	Deemed to satisfy Class A1	EC Decision 96/603/EC as amended		
Dimensional Variation:		EN12326-2:2011		
Slate Type:	Very Smooth    Smooth    Normal    Textured			
Deviation from flatness:	<1.0%			
Nominal thickness and variation:	5mm +/- 35%			
Deviation from declared width:	+/- 5mm			
Deviation from declared length:	+/- 5mm			
Deviation from straightness of edges:	+/- 5 mm			
Deviation from rectangularity:	+/- 1%			
Durability:				
Water absorption:	Code A1 0.36%	EN12326-2:2011		
Freeze thaw:	Not Required			
Thermal cycle test:	Code T1			
Carbonate content:	0.5%			
Sulphur dioxide exposure tests:	Code S1			
Non-carbonate carbon content:	0.5%	EN12326-2:2011		
Release of dangerous substances:	None in conditions of use as roofing or external cladding			
10. Declaration: The product(s) identified in Points 1 and 2 is in conformity with the declared performance under point 9. This declaration of performance is the sole responsibility of the manufacturer identified in point 4.				
Place & Date of Issue: PRIMERA SLATE COMPANY LIMITED 86 Ramsey Road, Warboys, Huntingdon, Cams PE28 2RW 1 <sup>st</sup> May 2020		Name: Mr Stephen Harding Position: Managing Director Signature: 		