



# BREATHABLE ROOF TILE UNDERLAY

## & SECONDARY BARRIER TO PREVENT THE INGRESS OF WIND DRIVEN RAIN, SNOW AND DUST

Danelaw® LR150 has been developed as a low resistance breathable roof tile and slate underlay. It is intended for use on pitched roofs as a secondary barrier installed beneath tiles and slates. It can be used unsupported draped over timber rafters or counter battens, or fully supported over timber sarking or rigid insulation.

### FEATURES AND BENEFITS

- BBA approved for use in warm and cold roofs
- Classified as LR (low resistance) in accordance with BS 5250
- Durable and resistant to damage from foot traffic
- UV resistant
- Temporary weather protection prior to tile or slate fixing
- Contributes to weathertightness of a completed roof
- Airtight when sealed for improved energy efficiency

### STANDARDS AND CERTIFICATION

- Complies with the requirements BS 5534 *Slating & Tiling for pitched roofs and vertical cladding. Code of practice*
- Complies with the ventilation requirements in BS 5250 *Standard & NHBC Standards Chapter 7.2*
- CE marked in accordance with BS EN 13859-1
- BBA approved certificate number 17/5426



### PRODUCT CODES AND SIZES


PRODUCT NAME	SIZE OF ROLL	PRODUCT CODE
Danelaw® LR150.....	1.0m x 50m .....	DLR150 1.0
Danelaw® LR150.....	1.5m x 50m .....	DLR150 1.5

The complete range of Danelaw® LR breathable roof tile underlays are independently tested by the BRE and zonal fixing approved by the BBA. The zonal suitability for Danelaw® LR150, when used unsupported as follows:

WIND UPLIFT RESISTANCE	ZONES				
	1	2	3	4	5
Batten Gauge @345mm	✓	✓	✓	-	-
Batten Gauge @250mm	✓	✓	✓	✓	✓

**NOTE 1:** Zone suitability applies only for underlays in applications where a well-sealed ceiling is present, ridge height is not greater than 15m, roof pitch is between 12.5° and 75°, site altitude is not greater than 100m, and no significant site topography is present. Other applications might require underlays with greater wind uplift resistance and it is advisable to seek professional advice.

**NOTE 2:** Zones 3 and 4 apply to Northern Ireland. Zone 3 applies to the Scilly Isles and Channel Islands. Zone 5 applies to the Shetland Islands.




## APPLICATION

The product should be installed in accordance with the manufacturer's installation guidelines and relevant clauses in BS 5534; *Slating and tiling for pitched roofs and vertical cladding Code of practice*, and BS 8000, *Workmanship on building sites, Code of practice for slating and tiling of roofs and walls*.


It is recommended that the ventilation guidelines in BS 5250, *Code of practice for control of condensation in buildings and NHBC Standards Chapter 7.2 Pitched Roofs* are followed. The level of roof ventilation required will depend on the building type, condensation risk, roof configuration and overall size of the roof

## DESIGN APPLICATIONS

Danelaw® LR150 can be installed draped over timber rafters or counter battens, or fully supported on sarking board or rigid insulation.



*Draped over rafters - cold roof*




*Draped over rafters - fully supported warm roof*

## TECHNICAL DATA

<b>DANELAW® LR150</b>	<b>PERFORMANCE</b>	EN 13859-1:2010 EN 13859-2:2010
Weight	150 gsm	
Roll length	50m	
Roll width	1.0m & 1.5m	
Resistance to water penetration [class]	W1	
Water vapour transmission properties [sd(m)]	0.020	
Resistance to penetration of air [m <sup>3</sup> /(m <sup>2</sup> x h x 50 Pa)]	0.040	
Tensile strength longitudinal / transverse [N/50mm]	350 / 210	
Elongation longitudinal / transverse [%]	60 / 75	
Resistance to tearing longitudinal / transverse [N]	150 / 160	
Reaction to Fire [class]	E	
Flexibility at low temperatures [°C]	- 40°C	
UV resistance [months]	3 months	


## RELATED PRODUCTS



*Rigid Support Tray*  
Product Code: HDRFST



*Roofing Underlay Support Tray*  
Product Code: HD 3000



**FOR ADDITIONAL HIGH VENTILATION**  
*Dry Fix Rollout Ridge and Hip*  
Product Code: HD ROR & HD CON



**FOR ADDITIONAL LOW VENTILATION**  
*Eaves and Soffits Vents*  
HD 12000U and HD 8000